## **DECLARATION OF PERFORMANCE**

## ACCORDING TO ANNEX IIICONSTRUCTION PRODUCTS REGULATIONS (305/2011/EU) & REGULATION (EU) NO. 574/2014

DOP NO: - AA3003-H24-(0.20 to 0.50)

- **01**. Unique identification code of the product type: **AA3003-H24-(0.20 to 0.50)**
- 02. Intended Use/es: Internal & External Load Bearing Structural & Constructional work.
- 03. Manufacturer: Hindalco Industries Ltd

Hirakud-FRP, HIRAKUD,

Sambalpur - Odisha

Pin-768016

- **04**. Authorised Representative : **None**
- 05. System/s of AVCP: System 2+
- 6a. Harmonised Standard: EN 15088:2005, Annex ZA.

## Notified body/ies:

TUV NORD systems GmbH and co. KG, D-22525 Hamburg, Kenn. Nr.0045 TUV NORD systems GmbH and co. KG, Notified body, Reg No. 0045 performed initial inspection of manufacturing plant under system 2+ and issued system of conformity of the factory production control.

6b. European Assessment document : Not Applicable

European Technical Assessment: Not Applicable

Technical Assessment Body: Not Applicable

Notified Body/ies: Not Applicable

## 09. DECLARED PERFORMANCE/s:

| Mandated/Essential<br>Characteristics | Performance  | Notes, expression of performance |
|---------------------------------------|--|----------------------------------|
| Tolerances on dimension and shape     | Flat Rolled Product  | Pass                             |
| Elongation                            | Minimum 2% Elongation on 50mm GL                           | Pass                             |
| Ultimate tensile strength             | 145-185 MPa in Transverse direction                        | Pass                             |
| Yeild Strength (0.2% OFFSET),<br>MPa  | 125 MPa Minimum in Transverse direction                    | Pass                             |
| Bendability                           | 2 T In 180 Degree<br>0.5 T In 90 Degree                    | Pass                             |
| Weldability                           | NO Performance Determined as not applicable to our product | -                                |
| Fatigue Strength                      | NO Performance Determined as not applicable to our product | -                                |
| Dangerous (regulated )<br>Substances  | < 50 PPM   | -                                |
| Durability<br>(against Corrosion)     | NO Performance Determined as not applicable to our product | -                                |

10. The performance of the product performance identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) no 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Authorized Representative

**Sudarsan Dutta** 

Place Issued: - Hindalco Industries Ltd.

Hirakud- FRP, Hirakud, Sambalpur – Odisha

Pin- 768016

Head-Quality Assurance